

ABSplus

for FORTUS 3D Production Systems

FORTUS
3D PRODUCTION SYSTEMS

Stratasys ABSplus is up to 40 percent stronger than standard Stratasys ABS material and is an ideal material for conceptual modeling, functional prototyping, manufacturing tools, and end-use-parts. The marriage of ABSplus with Fortus 3D Production Systems gives you the ability to create Real Parts™ direct from digital files that are stronger, smoother, and with high feature detail.



Mechanical Properties ¹	Test Method	Imperial	Metric
Tensile Strength, Type 1, 0.2 in/min	ASTM D638	5,200 psi	36 MPa
Tensile Modulus, Type 1, 0.2 in/min	ASTM D638	329,500 psi	2,265 MPa
Tensile Elongation, Type 1, 0.125 in/min	ASTM D638	4%	4%
Flexural Strength	ASTM D790	7,604 psi	52 MPa
Flexural Modulus	ASTM D790	319,737 psi	2,198 MPa
IZOD Impact, notched	ASTM D256	1.8 ft-lb/in	96 J/m


Thermal Properties ³	Test Method	Imperial	Metric
Heat Deflection Temperature @ 66 psi	ASTM D648	204° F	96° C
Heat Deflection Temperature @ 264 psi	ASTM D648	180° F	82° C
Coefficient of Thermal Expansion	ASTM D696	4.90 E -05 in/in/F	-----
Melt Point	-----	Not Applicable ²	Not Applicable ²

Other ³	Test Method	Value
Specific Gravity	ASTM D792	1.04

► See reverse for color options and system availability.

The information presented are typical values intended for reference and comparison purposes only. They should not be used for design specifications or quality control purposes. End-use material performance can be impacted (+/-) by, but not limited to, part design, end-use conditions, test conditions, etc. Actual values will vary with build conditions. Tested parts were built on Fortus 200mc @ 0.010" (0.254 mm) slice. Product specifications are subject to change without notice.

¹ Build orientation is on side long edge. ² Due to amorphous nature, material does not display a melting point. ³ Literature value unless otherwise noted.



System Availability	Layer Thickness Capability	Support Structure	Available Colors
Fortus 200mc	0.010 inch (0.254 mm) 0.007 inch (0.178 mm)	Soluble Supports	<ul style="list-style-type: none"> ■ Ivory ■ Black ■ Dark Grey ■ Red ■ Blue ■ Olive Green ■ Nectarine ■ Fluorescent Yellow

At the core: Advanced FDM® technology

Fortus systems are based on patented Stratasys FDM — Fused Deposition Modeling — technology. FDM is the industry's leading additive fabrication technology, and the only one that uses production grade thermoplastics, enabling the most durable parts.

Fortus systems use a wide range of thermoplastics with advanced mechanical properties so your parts can endure high heat, caustic chemicals, sterilization, and high impact applications.

No special facilities needed

You can install a Fortus 3D Production System just about anywhere. No special venting is required because Fortus systems don't produce noxious fumes, chemicals, or waste.

No special skills needed

Fortus 3D Production Systems are easy to operate and maintain compared to other additive fabrication systems because there are no messy powders or resins to handle and contain. They're so simple, an operator can be trained to operate a Fortus system in less than 30 minutes.

Get your benchmark on the future of manufacturing

Fine details. Smooth surface finishes. Accuracy. Strength. The best way to see the advantages of a Fortus 3D Production System is to have your own part built on a Fortus system. Get your free part at: www.fortus.com/benchmark.

For more information about Fortus systems, materials and applications, call **888.480.3548** or visit www.fortus.com

Fortus 3D Production Systems
Stratasys Incorporated
7665 Commerce Way
Eden Prairie, MN 55344
+1 888 480 3548 (US Toll Free)
+1 952 937 3000
+1 952 937 0070 (Fax)
www.stratasys.com
info@stratasys.com

Fortus 3D Production Systems
Stratasys GmbH
Weismüllerstrasse 27
60314 Frankfurt am Main
Germany
+49 69 420 9943 0 (Tel)
+49 69 420 9943 33 (Fax)
www.stratasys.com
europe@stratasys.com